

Art. LENNY

HS Code 54075200

Composition Surface - EU 1007/2011 100%PL

Composition Base - EU 1007/2011 100%PL

Weight m2 - DIN EN 12127 290 gr/m2 ($\pm$ 5%)

Piece lenght: 50 C.A. mt

Width: $\geq$ 140 cm

Abrasion Resistance (Martindale) - UNI EN ISO 12947-1 / UNI EN ISO 12947-2 119.000

Pilling Resistance - UNI EN ISO 12945-2 4/5

Resistance to seam slippage - UNI EN ISO 13936-2 weft 3.7mm warp 4.8mm

Fastness to rubbing - UNI EN ISO 105-X12 dry 4/5 wet 4/5

Fastness to light - UNI EN ISO 105-B02 5

Dimensional stability washing - UNI EN ISO 6330 weft -0.8% warp -0.6%

Dimensional stability dry - UNI EN ISO 3175-2 weft -1.0% warp -1.0%

Cigarette test - BS 5852 schedule 4 source 0 PART 1 Pass

Maintenance Symbols



Fabric treated with water repellent finish

Slight color tone differences might be possible

Test results were gathered from various samples and therefore represent average indicative values.

CERTIFICATION ISO 9001:2015 - N. 3906625
 CERTIFICATION ISO 14001:2015 - N. 3906846
 CERTIFICATION ISO 45001:2018 - N. 3906846



ISO 9001
 LL-C (Certification)



ISO 14001
 LL-C (Certification)



ISO 45001
 LL-C (Certification)



egoitaliano[®]
LIVING YOUR WAY

LENNY
Categoria
MICRO

E' il nuovo sostituto del New Kenya, un tessuto immediato, versatile e pratico. Ha una moltitudine di colori declinabili per ogni esigenza. E' dotato di trattamento antimacchia.

LENNY is the new substitute for New Kenya, an immediate, versatile and practical fabric. It has a multitude of colors to suit every need. It has a stain-resistant treatment